

Information letter

1 (5)

01 October 2009

UPM Raflatac Sheetstock Marketing

FSC Certified Matt Colour range

Dear Partner Merchant,

Following environmental market needs and looking for a better service and higher added value products, UPM Raflatac launches the new FSC certified coloured Vellum range. This new solution will replace the existing Matt Colour grades.

As per new grades we're also looking for a renewed shades, with more vivid and intense colours, meanwhile the same main technical properties remain on similar level,

Change in the range is forecasted to take effect during 4Q'2009, and it will be carried out gradually as our old stocks run out.

Old product	New FSC range	Adhesive	Sales code	Sheet size (cm)	W0 no score no backprint EAN code	W2 score, no backprint EAN code
Matt Yellow (LK)	Matt Yellow F cert MC (BEU)	Permanent (94-A)	BEU 94-A 39	50 x 70	7113685	7113692
Matt Green (LZ)	Matt Green F cert MC (BEV)	Permanent (94-A)	BEV 94-A 39	50 x 70	7113708	7113715
Matt Blue (LX)	Matt Blue F cert MC (BEX)	Permanent (94-A)	BEX 94-A 39	50 x 70	7113722	7113739
Matt Red (LY)	Matt Red F cert MC (BEY)	Permanent (94-A)	BEY 94-A 39	50 x 70	7113654	7113661

The updated product range and technical information sheets are also available in our web.

We kindly ask you to forward this information to the persons concerned in your organization.

Best Regards

UPM Raflatac Sheetstock Sales and Marketing

FSC (Forest Stewardship Council) is an international non-governmental organisation founded in 1993, whose task is to support environmentally appropriate, socially beneficial, and economically viable management of the world's forests. Forests certified against FSC standards are located in more than 60 countries. The Council has defined ten general principles of forest management. The actual certification standards are drawn up in accordance with the FSC principles in a national cooperation process. Fulfilling the FSC standard requires independent third-party verification. More information: www.fsc.org.

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC
TECHNICAL INFORMATION**

**SELF- ADHESIVE
FACE
UNCOATED PAPER**
**Product
Use**

01/09/2009

SHEETS

MATT YELLOW F cert MC

BEU

Woodfree pulp dyed SC paper

Eye catching display labels for price marking and promotional use.
Information labels printed on ink-jet, lasers and copiers.

Typical technical values

Substance	80	g/m ²	ISO 536	
Caliper	100	µm	ISO 534	
Tensile strength MD	5,0	kN/m	ISO 1924/1	
Tensile strength CD	3,3	kN/m	ISO 1924/1	
Roughness	2,4	microns	ISO 8791	PPS 10
Printability	Offset, flexography, letterpress, ink-jet, lasers and copiers.			
Additional info	Products named as F cert are registered to FSC SGS-COC-004879			

Warranty

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC
TECHNICAL INFORMATION**

SELF- ADHESIVE	01/09/2009
FACE	SHEETS
UNCOATED PAPER	MATT GREEN F cert MC
Product	BEV
Use	Woodfree pulp dyed SC paper
	Eye catching display labels for price marking and promotional use.
	Information labels printed on ink-jet, lasers and copiers.

Typical technical values

Substance	80	g/m ²	ISO 536
Caliper	100	µm	ISO 534
Tensile strength MD	5,0	kN/m	ISO 1924/1
Tensile strength CD	3,3	kN/m	ISO 1924/1
Roughness	2,4	microns	ISO 8791 PPS 10
Printability	Offset, flexography, letterpress, ink-jet, lasers and copiers.		
Additional info	Products named as F cert are registered to FSC SGS-COC-004879		

Warranty

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC
TECHNICAL INFORMATION**

SELF- ADHESIVE	01/09/2009 RLO
FACE	SHEETS
UNCOATED PAPER	MATT BLUE F cert MC
Product	BEX
Use	Woodfree pulp dyed SC paper Eye catching display labels for price marking and promotional use. Information labels printed on ink-jet, lasers and copiers.

Typical technical values

Substance	80	g/m ²	ISO 536
Caliper	100	µm	ISO 534
Tensile strength MD	5,0	kN/m	ISO 1924/1
Tensile strength CD	3,3	kN/m	ISO 1924/1
Roughness	2,4	microns	ISO 8791 PPS 10
Printability	Offset, flexography, letterpress, ink-jet, lasers and copiers.		
Additional info	Products named as F cert are registered to FSC SGS-COC-004879		

Warranty

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.

01 October 2009

UPM Raflatac Sheetstock Marketing

**UPM RAFLATAC
TECHNICAL INFORMATION**

SELF- ADHESIVE	01/09/2009
FACE	SHEETS
UNCOATED PAPER	MATT RED F cert MC
Product	BEY
Use	Woodfree pulp dyed SC paper Eye catching display labels for price marking and promotional use. Information labels printed on ink-jet, lasers and copiers.

Typical technical values

Substance	80	g/m ²	ISO 536	
Caliper	100	µm	ISO 534	
Tensile strength MD	5,0	kN/m	ISO 1924/1	
Tensile strength CD	3,3	kN/m	ISO 1924/1	
Roughness	5,5	microns	ISO 8791	PPS 10
Printability	Offset, flexography, letterpress, ink-jet, lasers and copiers.			
Additional info	Products named as F cert are registered to FSC SGS-COC-004879			

Warranty

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot take responsibility for any damage caused through their use.

This technical sheet replaces all previous versions. All information is subject to change without notice.