



High Gloss White FSC Certified

Sustainable business from premium sustainable labelling

The new FSC Certified High Gloss White meets market demand for environmentally responsible labelling that satisfies the highest quality standards. It also improves over the original High Gloss White with higher weight, whiteness and brightness.

Combined with our standard sheet adhesives, High Gloss White F Cert MC is suitable for a wide range of end-uses requiring an excellent high-gloss foundation for premium-quality print work.

- FSC certified from sustainably managed forests
- Higher whiteness and brightness.
- 84 gr/m², mirror-like gloss for highest quality labels

The new solution will replace the existing High Gloss White grades. Change in the range is forecasted to take effect from April 2011, and it will be carried out gradually as our old stocks run out.

EAN Code	Sales Code	Combination	Sheet size
7120188	BWG 94-A 39 W3	High Gloss White F Cert MC / 94-A / Kraft 90	64 x 45
7120263	BWG 94-A 39 W0	High Gloss White F Cert MC / 94-A / Kraft 90	50 x 70
7120225	BWG 94-A 39 W1	High Gloss White F Cert MC / 94-A / Kraft 90	50 x 70
7120171	BWG 94-A 39 W3	High Gloss White F Cert MC / 94-A / Kraft 90	50 x 70
7120232	BWG 94-A 39 W1	High Gloss White F Cert MC / 94-A / Kraft 90	100 x 70
7120195	BWG 94-A 39 W3	High Gloss White F Cert MC / 94-A / Kraft 90	100 x 70
7120249	BWG 98-H 39 W1	High Gloss White F Cert MC / 98-H / Kraft 90	50 x 70
7120201	BWG 98-H 39 W3	High Gloss White F Cert MC / 98-H / Kraft 90	50 x 70
7120256	BWG 98-H 39 W1	High Gloss White F Cert MC / 98-H / Kraft 90	100 x 70
7120218	BWG 90-R 39 W3	High Gloss White F Cert MC / 90-R / Kraft 90	50 x 70
7120270	BWG 98-H 2J W0	High Gloss White F Cert MC / 98-H / Kraft 180	50 x 70

MASTERTAC TECHNICAL INFORMATION

03/2011 ENG

SELF-ADHESIVE	SHEETS
FACE	HIGH GLOSS WHITE F cert MC
Gloss Coated	BWG (sales code)
Product	Cast-coated, wood-free paper with mirror-like gloss finish.
Use	For high quality multicolour, glossy product labels.

Typical technical values

Substance	84	g/m ²	ISO 536	
Caliper	86	µm	ISO 534	
Tensile strength MD	5.3	kN/m	ISO 1924/I	
Tensile strength CD	3.1	kN/m	ISO 1924/I	
Brightness	93	%	ISO 2470/I	
Roughness	0,5	microns	ISO 8791	PPS 10
Gloss	90	%	Hunter 75°	
Opacity	90	%	ISO 2471	
Whiteness	130	%	ISO 11475	

Printability Flexography, letterpress, rotogravure, offset, screen and hot foil.

Approvals Products named as F cert MC are registered to SGS-COC-004879 FSC™ mixed credit.

Warranty Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use.

This publication replaces all previous versions. All information is subject to change without notice.