



## Jetlaser Multitac M

Jetlaser Multitac M is a versatile solution for numerous labelling applications requiring labels that are removable from one surface and transferable to another.

This multi-layer construction consists of an uncoated, white paper label face on top of two kraft liners which have a permanent adhesive between them. Peel and stick, peel and stick again. Jetlaser Multitac M is printable with monochrome and multicolour inkjets, laser printers and copiers.

Logistics, tracking and tracing, stock keeping and quality control process all benefit from the ease and efficiency offered by Jetlaser Multitac M. Online business is another area of high demand, and the applications also range from retail labelling to pharmaceutical and decorative uses.

Combination	Sales code	Size (cm)	Packaging	Minimum order quantity (sheets, wrapped)	Sheet EAN code No score, no back-print (W0)
Jetlaser Multitac M	FGZMPA41XW0	32x45	Box (200 sheets)	2400	7161662
		64x45	Ream (125 sheets)	2500	7161686
		50x70	Ream (125 sheets)	2500	7161679

For more information, please contact your Area Sales Manager or Customer Service.

# MASTERTAC TECHNICAL INFORMATION

08/2016 ENG

## PRODUCT JETLASER MULTITAC M

JETLASER + MPA4 + Kraft 55 + MPA4 + Kraft 55

Sales code FGZ/MPA4/1X

EAN 6415788010136

Product use Logistics, tracking and tracing, stock keeping and quality control process, Online business and retail labelling to pharmaceutical and decorative uses.

A versatile solution for numerous labelling applications requiring labels that are removable from one surface and transferable to another.

## FACE JETLASER

Product	Woodfree machine-finished paper.		
Substance	70	g/m <sup>2</sup>	ISO 536
Caliper	89	µm	ISO 534
Opacity	92	%	ISO2471
Brightness	98	%	ISO2470/1
Tensile strength MD	5,5	kN/m	ISO 1924
Tensile strength CD	2,3	kN/m	ISO 1924
Stiffness MD	0,28	kN/m	ISO/DP2493
Stiffness CD	0,1	kN/m	ISO/DP2493
Printability	Ink jet, laser and copier. Flexography, letterpress, offset and screenprint. Please note that conventional printing can compromise inkjet and laser overprintability.		

## ADHESIVE MPA4

Type	Clear permanent adhesive.		
Composition	Acrylic, water borne.		
Tack min	9	N	FTM 9
PE-looptack min	8	N	Modified FTM 9

## BACKING KRAFT 55

Product	White woodfree kraft backing paper.		
Substance	51	g/m <sup>2</sup>	ISO 536
Caliper	54	µm	ISO 534
Tensile strength MD	4,7	kN/m	ISO 1924
Tensile strength CD	2,0	kN/m	ISO 1924

## PERFORMANCE

Total caliper	228	µm	
Minimum labelling temperature	5	°C	
Service temperature	-20 to 100	°C	
Shelf life	From the date of manufacture: 4 years at +20 °C and RH 50%. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.		

## Disclaimer

Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. This publication replaces all previous versions. All information is subject to change without notice.