



Master[®]tac

The smart choice.

New digital film product: PETLASER GLOSS CLEAR HS + REMOVABLE ADHESIVE

UPM Raflatac continues to meet your latest digital challenges with a new peelable labelling solution – **Petlaser Gloss Clear HS with a removable adhesive**.

This gloss transparent product is ideal for a wide range of removable labelling applications: Shop window signage, product labelling from open-closure labels to bottle labelling, and promotional uses among many others.

Combination	Sales code	Size (cm)	Packaging	MOQ	Sheet EAN code
				Wrapped	Solid unprinted backing (W0)
Petlaser Gloss Clear HS	CBQ/97-R/FGY/W0	32 x 45	Box – 250 sh	5000	7168623
			Box – 100 sh	5000	7168647

For further information, please contact your UPM Raflatac Area Sales Manager and/or Customer Service. Also enquire about other removable digital film options like **Petlaser Matt White HS**.

Master[®]tac

MASTERTAC TECHNICAL INFORMATION

PRODUCT PETLASER GLOSS CLEAR HS + REMOVABLE ADHESIVE

Petlaser Gloss Clear HS + DR29 + Kraft Special Stabilized 120

Sales code CBQ/97-R/FGY/W0

FACE PETLASER GLOSS CLEAR HS (CBQ)

Product	Transparent, gloss coated heat stabilized polyester film.		
Product use	Information labelling where overprinting is made by laser or thermal transfer. Specially developed for medium and high volume laser printers.		
Substance	71	g/m ²	DIN 53352
Caliper	50	µm	DIN 53370
Elongation MD	155.0	%	DIN 53455
Elongation CD	110.0	%	DIN 53455
Printability	Due to the pre-treatment, the film is printable by common label printing methods like letterpress, flexography, screen and offset. Special inks designed for non-absorbent materials should be used. Laser and copier printable: specially developed for medium and high volumes.		

ADHESIVE 97R (97-R)

Type	Removable adhesive for filmic labels.			
Composition	Acrylic, water borne.			
Use	Specially designed for filmic face materials in Cut Size segment applications. Good removability, UV-stability (non-yellowing), clarity and water resistance once labeled.			
Tack min	9	N	FTM 9	
Tack max	8	N	FTM 9	
Shear min	8	N	FTM 9	
Peel min	1.5	N/25mm	FTM 2	90°
Peel max	6.0	N/25mm	FTM 2	90°
Labelling temperature min	5	°C		
Service temperature	-10 to 80	°C		

BACKING KRAFT STABILIZED 120 (FGX)

Product	White woodfree kraft backing paper.			
Product use	Designed for all laser end-uses, specially for high-speed printing and filmic label faces where high stiffness and excellent lay-flat properties is demanded.			
Substance	120	g/m ²	ISO 536	
Caliper	112	µm	ISO 534	
Tensile strength MD	8.0	kN/m	ISO 1924	
Tensile strength CD	4.0	kN/m	ISO 1924	

Disclaimer

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.